




# QCC nVent ERIFLEX Flexibar Clamp



- Connects nVent ERIFLEX Flexibar to punched busbar
- Allows for excellent electrical contact
- Compact, space saving design
- Installs quickly and easily
- Ideal for on site modifications



Material: Steel  
Finish: Electrogalvanized



Part Number	Article Number	Conductor Width	Depth D	Height H	Width W	Thickness T	A	B	C	Unit Weight
QCC15-5-32	561210	15.5 – 32.0 mm	13 mm	35 mm	70 mm	5 mm	50 mm	10.5 mm	11 mm	0.112 kg
QCC40-63	561220	40.0 – 63.0 mm	13 mm	35 mm	95 mm	5 mm	75 mm	10.5 mm	11 mm	0.158 kg

Use one clamp when nVent ERIFLEX Flexibar thickness is less than 5 mm [0.2"] and two clamps when nVent ERIFLEX Flexibar thickness is greater than 5 mm [0.2"].

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.