

## EC35 Earthing/Grounding Connector





- Very compact clamp for connecting cable conductors to earthing busbar without drilling •
- Conductor is clamped with a pressure plate ٠
- ٠ Clamps can be mounted and slid into position on busbar prior to connecting conductors
- ٠ Connections can be added after busbar has been mounted
- Single screw locks clamp and makes connection
- EAC compliant
- ٠ RoHS compliant





Finish: Electrogalvanized Material: Steel Busbar Thickness: 4 – 5 mm Busbar Width: 12 mm



Part Number	Article Number	Conductor Size	Depth D	Height H	Width W	Torque TQ	Unit Weight
EC35	553470	2.5 mm² Solid - 35 mm² Stranded	11.5 mm	27 mm	31 mm	6 N-m	0.025 kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved nVent, nVent CADDY, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

