


# BS-125A Four Pole Insulating Support



- Create custom four pole distribution blocks for an electrical distribution system
- Protection screen can be attached directly to the support
- Includes screws to mount threaded copper busbars
- Clips on to DIN rail using DR-CLIP or mounts with screws
- Halogen free
- RoHS compliant



Material: Steel, Glass Fibre Reinforced Polyamide  
 Finish: Electrogalvanized  
 Max Working Voltage, IEC (Ui): 1,000 VAC, 1,500 VDC  
 Working Temperature: -40 to 130 °C  
 Typical Application Current Rating: 125 – 160 A  
 Complies With: IEC® 60439.1, IEC® 61439.1,  
 IEC® 60695-2-11 (Glow Wire Test 960 °C)  
 Flammability Rating: UL® 94V-0



Part Number	Article Number	Busbar Width	Busbar Thickness	Depth D	Height H	Screw Diameter Sc	Unit Weight
BS-125A	551311	12 – 15 mm	4 – 5 mm	117.5 mm	126 mm	M5	0.1 kg

Must be used with copper busbars.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.