



BS-250A Four Pole Insulating Support



- Create custom four pole distribution blocks for an electrical distribution system
- Mounts with screws
- Protection screen can be fixed using spacers
- Halogen free
- RoHS compliant



Material: Steel, Glass Fibre Reinforced Polyamide

Finish: Electrogalvanized

Max Working Voltage, IEC (Ui): 630 VAC, 630 VDC

Working Temperature: -40 to 130 °C

Typical Application Current Rating: 160 – 250 A

Complies With: IEC® 60439.1, IEC® 61439.1,

IEC® 60695-2-11 [Glow Wire Test 960 °C]

Flammability Rating: UL® 94V-0



Part Number	Article Number	Busbar Width	Busbar Thickness	Depth D	Height H	A	Screw Diameter Sc	Unit Weight
BS-250A	551300	15 – 20 mm	5 mm	45 mm	150 mm	130 mm	M6	0.05 kg

Must be used with copper busbars.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.