





# Adjustable Flat Busbar Support Kit



- Kit includes rail, insulators and mountable extension arms
- Adjustable distances between phases
- Adjusts quickly to accommodate multiple busbar thicknesses
- High resistance to short-circuit forces
- Provides excellent electrical protection for equipment
- Three phase with neutral circuit
- Halogen free
- RoHS compliant



Material: Steel, Aluminum, Glass Fibre Reinforced Polyamide

Max Working Voltage, IEC (Ui): 1,000 VAC, 1,500 VDC

Working Temperature: -40 to 130 °C

Complies With: IEC® 60439.1, IEC® 61439.1,

IEC® 60695-2-11 [Glow Wire Test 960 °C]

Flammability Rating: UL® 94V-0

Busbar Width: 30 – 80 mm

Busbar Thickness: 5 – 10 mm



Part Number	Article Number	Height H	Width W	A	B	C	Screw Diameter Sc	Unit Weight
AFBS-B600	504971	70 mm	549 – 749 mm	507 mm	61 – 176 mm	525 – 725 mm	M8	2.2 kg

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.