



Universal Busbar Support with Neutral Circuit, High Ampacity



- Universal fixing system
- Installs quickly and easily
- Extremely robust construction
- Screws are made from non-magnetic stainless steel
- Halogen free insulators



Material: Steel, Glass Fibre Reinforced Polyamide
 Max Working Voltage, IEC (Ui): 1,000 VAC, 1,500 VDC
 Working Temperature: -40 to 130 °C
 Complies With: IEC® 60439.1, IEC® 61439.1,
 IEC® 60695-2-11 (Glow Wire Test 960 °C)
 Flammability Rating: UL® 94V-0



Part Number	Article Number	Busbars per Phase	Busbar Width	Busbar Thickness	Width W	A
Typical Application Current Rating: 3,500 A						
UBS1-10TN-160	561500	1	160 mm	10 mm	300 mm	70 mm
Typical Application Current Rating: 5,700 A						
UBS2-10TN-160	561870	1 – 2	160 mm	10 mm	480 mm	110 mm
UBS2-10TN-200	561880	1 – 2	200 mm	10 mm	480 mm	110 mm
Typical Application Current Rating: 7,400 A						
UBS3-10TN-160	561540	1 – 3	160 mm	10 mm	480 mm	110 mm
UBS3-10TN-200	561550	1 – 3	200 mm	10 mm	480 mm	110 mm

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.