

FRCB Flat Braid in Coil, Plain Copper



- Braids in coil are mainly used for power distribution or earthing applications
- Non-magnetic material

Material: Copper



Part Number	Article Number	Nominal Current	Cross Section	Number of Wires	Wire Diameter	Length	Thickness	Width	Unit Weight
FRCB15-5	557010	45 A	5 mm ²	288	0.15 mm	25 m	1.0 mm	8 mm	0.05 kg
FRCB15-10	557030	75 A	10 mm ²	576	0.15 mm	25 m	1.5 mm	10 mm	0.10 kg
FRCB15-16	557040	120 A	16 mm ²	896	0.15 mm	25 m	1.5 mm	15 mm	0.16 kg
FRCB15-20	557050	140 A	20 mm ²	1,120	0.15 mm	25 m	1.5 mm	20 mm	0.20 kg
FRCB15-25	557060	150 A	25 mm ²	1,404	0.15 mm	25 m	1.5 mm	23 mm	0.25 kg
FRCB15-35	557080	200 A	35 mm ²	1,980	0.15 mm	25 m	2.5 mm	23 mm	0.35 kg
FRCB15-40	557090	220 A	40 mm ²	2,272	0.15 mm	25 m	2.5 mm	25 mm	0.40 kg
FRCB15-50	557100	250 A	50 mm ²	2,848	0.15 mm	25 m	3.0 mm	28 mm	0.50 kg
FRCB15-70	557120	290 A	70 mm ²	3,968	0.15 mm	25 m	3.5 mm	30 mm	0.70 kg
FRCB15-75	557130	300 A	75 mm ²	4,256	0.15 mm	25 m	4.0 mm	30 mm	0.75 kg
FRCB15-100	557150	360 A	100 mm ²	5,664	0.15 mm	25 m	4.0 mm	40 mm	1.00 kg

Unit weight is per meter [3.28'].

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.