


FSSB Flat Braid in Coil, Stainless Steel



- High-quality durable stainless steel 316L provides superior abrasion, corrosion, chemical, and UV resistance for outdoor and corrosive applications
- Non-magnetic material
- Durability of product lengthens cycle time between maintenance

Material: Stainless Steel 316L (EN 1.4404)



Part Number	Article Number	Cross Section	Wire Diameter	Length	Thickness	Width	Unit Weight
FSSB25-16	557160	16 mm ²	0.25 mm	25 m	1.5 mm	15 mm	0.14 kg
FSSB25-25	557170	25 mm ²	0.25 mm	25 m	1.5 mm	23 mm	0.22 kg
FSSB25-50	557390	50 mm ²	0.25 mm	25 m	3.0 mm	30 mm	0.44 kg

Unit weight is per meter [3.28'].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.