

# RRCB Round Braid in Coil, Plain Copper



- Braids in coil are mainly used for power distribution or earthing applications
- Non-magnetic material

Material: Copper



Part Number	Article Number	Nominal Current	Cross Section	Number of Wires	Wire Diameter	Length	Diameter	Unit Weight
RRCB15-6	557400	45 A	6 mm <sup>2</sup>	352	0.15 mm	25 m	4 mm	0.06 kg
RRCB15-10	557420	75 A	10 mm <sup>2</sup>	560	0.15 mm	25 m	5 mm	0.10 kg
RRCB15-16	557430	120 A	16 mm <sup>2</sup>	900	0.15 mm	25 m	6 mm	0.16 kg
RRCB15-25	557440	150 A	25 mm <sup>2</sup>	1,416	0.15 mm	25 m	8 mm	0.25 kg
RRCB15-30	557450	180 A	30 mm <sup>2</sup>	1,680	0.15 mm	25 m	9 mm	0.30 kg
RRCB15-50	557460	250 A	50 mm <sup>2</sup>	2,820	0.15 mm	25 m	11 mm	0.50 kg
RRCB15-75	557470	300 A	75 mm <sup>2</sup>	4,236	0.15 mm	25 m	14 mm	0.75 kg
RRCB15-100	557480	360 A	100 mm <sup>2</sup>	5,652	0.15 mm	25 m	18 mm	1.00 kg

Unit weight is per meter (3.28').

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.