

RTCB Round Braid in Coil, Tinned Copper



Material: Copper
Finish: Tinned



Part Number	Article Number	Nominal Current	Cross Section	Number of Wires	Wire Diameter	Length	Diameter	Unit Weight
RTCB15-6	557600	45 A	6 mm ²	352	0.15 mm	25 m	4.0 mm	0.06 kg
RTCB15-8	557610	65 A	8 mm ²	464	0.15 mm	25 m	4.5 mm	0.08 kg
RTCB15-10	557620	75 A	10 mm ²	560	0.15 mm	25 m	5.0 mm	0.10 kg
RTCB15-10HL	503700	75 A	10 mm ²	560	0.15 mm	100 m	5.0 mm	0.10 kg
RTCB15-16	557630	120 A	16 mm ²	900	0.15 mm	25 m	6.0 mm	0.16 kg
RTCB15-16HL	503710	120 A	16 mm ²	900	0.15 mm	100 m	6.0 mm	0.16 kg
RTCB15-25	557640	150 A	25 mm ²	1,416	0.15 mm	25 m	8.0 mm	0.25 kg
RTCB15-25HL	503720	150 A	25 mm ²	1,416	0.15 mm	100 m	7.5 mm	0.25 kg
RTCB15-30	557650	180 A	30 mm ²	1,680	0.15 mm	25 m	9.0 mm	0.30 kg
RTCB15-50	557660	250 A	50 mm ²	2,820	0.15 mm	25 m	11.0 mm	0.50 kg
RTCB15-75	557670	300 A	75 mm ²	4,236	0.15 mm	25 m	13.5 mm	0.75 kg
RTCB15-100	557680	360 A	100 mm ²	5,652	0.15 mm	25 m	17.0 mm	1.00 kg

Unit weight is per meter [3.28'].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.