

RTCBI Insulated Round Braid in Coil, Tinned Copper



Material: Copper, Polyvinylchloride
Finish: Tinned



| Part Number | Article Number | Nominal Current | Cross Section | Number of Wires | Wire Diameter | Length | Diameter | Unit Weight |
|-------------|----------------|-----------------|--------------------|-----------------|---------------|--------|----------|-------------|
| RTCBI15-10 | 503400 | 75 A | 10 mm ² | 560 | 0.15 mm | 25 m | 7.0 mm | 0.12 kg |
| RTCBI15-16 | 503410 | 120 A | 16 mm ² | 900 | 0.15 mm | 25 m | 8.0 mm | 0.18 kg |
| RTCBI15-25 | 503420 | 150 A | 25 mm ² | 1,416 | 0.15 mm | 25 m | 9.5 mm | 0.25 kg |
| RTCBI15-30 | 503430 | 180 A | 30 mm ² | 1,680 | 0.15 mm | 25 m | 10.0 mm | 0.35 kg |
| RTCBI15-50 | 503440 | 250 A | 50 mm ² | 2,820 | 0.15 mm | 25 m | 12.5 mm | 0.58 kg |

| Insulation Thickness | Insulation Voltage | Temperature | Flammability Rating |
|----------------------|--------------------|-------------|---------------------|
| 1 mm | 450 V | 70 °C Max | UL® 94V-0 |

Unit weight is per meter [3.28'].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.